



24VDC



MB24 MBE24

**CONTROL UNITS:**

MBE24 ——— CP.MBY24
MB24 ——— BRAINY24+
 BRAINY24

ARTICULATED ARM

with integrated control unit
 personalised release key

up to 2.5 m**BENINCA**



100%
 Made in Italy

**24 Vdc** | intensive use

- 24 Vdc self-locking electromechanical operator for intensive use equipped with strong, articulated and anti-shearing arm
- Suitable for gates installed on large posts
- Tempered steel mechanical features to guarantee sturdiness and solidity
- Operation guaranteed even in the event of a power supply failure through batteries
- Amperometric sensor obstacle detection system to prevent crushing
- Equipped with open and close limit switches
- Option of adjustable wire unlock device that allows opening from the outside in the event of a power supply failure

Arm not included

www.beninca.com



A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	α
0	470	350	243	140	90°
50	470	339	255	140	90°
100	470	331	262	140	90°
150	470	328	264	140	90°
185	470	356	237	160	90°
200	440	410	160	200	90°
0	420	244	318	200	110°
100	420	262	310	200	105°

BENINCA**COMPLETE KITS**

MOTOR 1
 1x **MBE24**



MOTOR 2
 1x **MB24**



ARMS
 2x **BA**



PHOTOCELLS
 1x **PUPILLA.R**



FLASHING LIGHT
 1x **LAMPI.LED**



SELECTOR
 1x **TOKEY**



TRANSMITTER
 1x **TO.GO2VA**

KMB24



BA
Single arm.



BS
Sliding arm.




MB.CP2
Set of counter plates for two operators, suitable for the installation on columns made of stones.



MB.SE
Externally fitted anti-intrusion cable unlock device which allows the gate to be unlocked from outside.



DU.V96
12 Vac/dc vertical electric lock, supplied with counterplate. Permits internal/external release.



DU.V90
12 Vac/dc horizontal electric lock, supplied with counterplate. Permits internal/external release.



DU.9990
Covering plate for DU.V90.



ID.TA
Warning board.



IRI.TX4VA
4-channel transmitter with Advanced Rolling Code and Rolling Code.

IRI.TX4AK
4-channel transmitter with Advanced Rolling Code and Fixed Code.



IRI.LAMP
White full range flashing light, 20-255 VAC with built-in aerial.




IRI.KPAD
Battery operated wireless vandal-proof digital keypad with alert buzzer and backlit buttons. Triple coding: Rolling Code, Programmable Code and Advanced Rolling Code. 254 memorisable codes.




IRI.CELL
Pair of vandal-proof metal covers for PUPILLA/PUPILLA.R photocells, comprising front and rear shells with concealed screw. They can maintain perfect orientation over 180°.



PUPILLA
Pair of photocells adjustable to 180°. Option to synchronise up to 4 pairs, 24 VAC/DC power supply. Easy adjustment through a LED that signals optimal alignment. Compact size: 36x110x35 mm



BRAINY24.CB-SW
Accessory equipped with 1.2 Ah batteries and support bracket.



BRAINY24.CB
Accessory with CBY.24V battery charger, 1.2 Ah batteries and support bracket.



CBY.24V
Battery charger card. The CBY.24V card allows charging two different types of nickel metalhydride and lead batteries.



DA.BT2
2.1Ah 12 Vdc Battery.

DA.BT6
7Ah 12 Vdc Battery.



LB
Standard box for control units. Protection level IP55. (290 x 220 x 118 mm)

AUTOMATISMI BENINCA SpA • Via del Capitello, 45 • 36066 Sandrigo (VI) ITALY • T +39 0444 751030 • sales@beninca.com

TECHNICAL DATA	MB24	MBE24
Power supply	---	230 Vac (50-60Hz)
Motor supply	24 Vdc	24 Vdc
Max absorbed current	6.2 A	0.76 A
Torque	180 Nm	180 Nm
Opening time	10"	10"
Duty cycle	intensive use	intensive use
Protection level	IP44	IP44
Built-in control unit	NO	YES
Operating temperature	-20°C /+50°C	-20°C /+50°C
Leaf max dimension	2.5 m	2.5 m
Weight	8.2 kg	10.7 kg
Items no. per pallet	39	39
Kit weight	25.4 kg	25.4 kg
Kits no. per pallet	12	12